

Elettropompe sommerse per pozzi da 8" - 12" (200 - 300 mm)

Electric submersible pumps for 8" - 12" (200 - 300 mm) wells



Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

P o r t a t a • F l o w

50 Hz M = 1- 230 V T = 3- 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		P o r t a t a • F l o w																		
	HP	KW	A	µF	m	DNM	m³/h	0	30	36	42	48	60	72	84	90	l/min	0	500	600	700	800	1000	1200	1400

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante semiassiale • Semi-Axial impeller																												
6TA10	2/1500	10	7,5	16,5	3	4"	40	36	35	34	32	27	22	16	11													
6TA15	3/1500	15	11	24	3	4"	60	54	52	50	47	41	32	23	17													
6TA20	4/1500	20	15	31,5	3	4"	79	72	69	66	62	54	43	30	23													
6TA25	5/1500	25	18,5	38	3	4"	98	89	85	81	77	67	54	38	28													
6TA30	6/1500	30	22	47,3	3	4"	117	107	103	98	93	80	65	46	35													
6TA35	7/1500	35	26	54	3	4"	137	124	119	114	108	94	76	53	40													
6TA40	8/1500	40	30	61,6	3	4"	154	141	136	130	123	107	85	60	45													
8TA50	10/1500	50	37	71,5	3,5	4"	191	177	171	163	153	132	106	72	54													

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
6TA10	2/1500	1439	967	190	87,5
6TA15	3/1500	1656	1062	190	107
6TA20	4/1500	1858	1142	190	125
6TA25	5/1500	2080	1242	190	144
6TA30	6/1500	2332	1372	190	163,5
6TA35	7/1500	2643	1606	190	200,5
6TA40	8/1500	2709	1512	190	198,5
8TA50	10/1500	2915	1519	190	276

