

# Elettropompe sommerse per pozzi da 4" (100 mm)

## Electric submersible pumps for 4" (100 mm) wells

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Flow

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Portata • Flow																
	HP	KW	A	µF	m	DNM	m <sup>3</sup> /h	0	3	4,5	6	7,5	9	10,5	11,4	l/min	0	50	75	100	125	150	175

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante semiassiale • Semi-Axial impeller																										
Model	Flow	HP	KW	A	µF	m	DNM																			
4M10	5/190	1	0,75	6	25	2	2"	32	28	25	22	17	12	6	2											
4M15	8/190	1,5	1,1	8	31,5	2	2"	51	45	40	34	27	19	9	3											
4M20	11/190	2	1,5	11	40	2	2"	70	62	55	47	38	26	13	4											
4M30	17/190	3	2,2	15,9	60	2	2"	108	95	85	73	58	41	20	6											
4T10	5/190	1	0,75	2,3		2	2"	32	28	25	22	17	12	6	2											
4T15	8/190	1,5	1,1	3,2		2	2"	51	45	40	34	27	19	9	3											
4T20	11/190	2	1,5	4,2		2	2"	70	62	55	47	38	26	13	4											
4T30	17/190	3	2,2	5,7		2	2"	108	95	85	73	58	41	20	6											
4T40	25/190	4	3	7,6		2	2"	163	149	135	115	92	65	35	15											
4T55	32/190	5,5	4	10		3	2"	209	191	173	147	117	83	45	19											
4T75	43/190	7,5	5,5	12,5		4	2"	281	256	233	198	158	112	60	26											

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4M10	5/190	806	441	95	14,5
4M15	8/190	965	471	95	17
4M20	11/190	1144	521	95	19,7
4M30	17/190	1558	677	95	28,5
4T10	5/190	776	411	95	13,1
4T15	8/190	935	441	95	15,7
4T20	11/190	1094	471	95	17,7
4T30	17/190	1402	521	95	22
4T40	25/190	1886	617	95	29,7
4T55	32/190	2247	677	95	34,9
4T75	43/190	2810	767	95	42,9

