

Elettropompe sommerse per pozzi da 4" (100 mm) 60Hz

Electric submersible pumps for 4" (100 mm) wells 60 Hz

Caratteristiche tecniche 2 poli 60 Hz • Performance characteristics 2 poles 60 Hz

60 Hz M = 1~ 230 V T = 3~ 400 V		Caratteristiche Nominali Nominal Characteristics HP KW A μ F		Cavo Cable m DNM		P o r t a t a • F l o w															
						m ³ /h	l/min	0	3	4,5	6	7,5	9	10,5	11,4	13,5					
						P r e v a l e n z a m a n o m e t r i c a t o t a l e i n m e t r i • T o t a l m a n o m e t r i c h e a d i n m e t e r s															
Girante semiassiale • Semi-Axial impeller																					
4M20	5/190	2	1,5	11	35	2	2"	47	45	42	38	33	28	22	18	8					
4M30	8/190	3	2,2	15,2	50	2	2"	77	71	66	59	51	41	32	27	11					
4T20	5/190	2	1,5	3,8		2	2"	47	45	42	38	33	28	22	18	8					
4TH30	8/190	3	2,2	5,4		2	2"	77	71	66	59	51	41	32	27	11					
4T40	11/190	4	3	7		2	2"	105	99	92	83	72	60	47	38	16					
4T55	17/190	5,5	4	9,4		3	2"	162	147	138	125	108	88	67	55	21					
4T75	25/190	7,5	5,5	12		4	2"	230	214	202	183	157	129	99	81	29					

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4M20	5/190	886	521	95	17,9
4M30	8/190	1171	677	95	25,7
4T20	5/190	836	471	95	15,6
4TH30	8/190	1065	571	95	20,6
4T40	11/190	1240	617	95	24,6
4T55	17/190	1558	677	95	29,4
4T75	25/190	2036	767	95	37,1

