

Elettropompe sommerse per pozzi da 8" - 12" (200 - 300 mm)

Electric submersible pumps for 8" - 12" (200 - 300 mm) wells



Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Flow

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Portata • Flow										
	HP	KW	A	µF	m	DNM	m³/h	0	42	48	60	72	84	90	96	108	120
							l/min	0	700	800	1000	1200	1400	1500	1600	1800	2000

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante semiassiale • Semi-Axial impeller							Prevalenza manometrica totale in metri • Total manometric head in meters											
6TA75	1/2000	7,5	5,5	12,8	3	4"	20,5	19	18	17,5	16	14,5	13,5	12	9	5,5		
6TA125	2/2000	12,5	9,2	19,7	3	4"	40	37	36	34	31	27,5	25,5	23	17	11		
6TA20	3/2000	20	15	31,5	3	4"	62	57	55	52	48	43	40	36	27	17		
6TA25	4/2000	25	18,5	38	3	4"	79	74	72	68	62	55	51	46	34	22		
6TA35	5/2000	35	26	54	3	4"	103	95	92	87	80	70	65	59	45	29		
6TA40	6/2000	40	30	61,6	3	4"	123	114	111	104	96	86	80	72	54	35		
8TA50	7/2000	50	37	71,5	3,5	4"	144	133	130	122	112	98	90	82	63	40		
8TA50	8/2000	50	37	71,5	3,5	4"	158	150	145	135	124	110	101	91	68	43		
8TA60	9/2000	60	45	85,9	3,5	4"	185	170	166	156	144	129	120	108	81	52		
8TA75	10/2000	75	55	106	3,5	4"	205	190	185	173	160	143	133	120	90	57		
8TA75	11/2000	75	55	106	3,5	4"	226	209	203	191	176	158	146	132	99	63		

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
6TA75	1/2000	1172	917	182	69
6TA125	2/2000	1397	1007	182	87,5
6TA20	3/2000	1667	1142	182	112
6TA25	4/2000	1902	1242	182	131
6TA35	5/2000	2401	1606	182	180
6TA40	6/2000	2442	1512	182	177,5
8TA50	7/2000	2426	1350	185	236
8TA50	8/2000	2561	1350	185	245
8TA60	9/2000	2776	1430	185	270
8TA75	10/2000	3011	1530	185	300
8TA75	11/2000	3146	1530	185	309

