

Elettropompe sommerse per pozzi da 6" (150 mm)

Electric submersible pumps for 6" (150 mm) wells

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Flow

50 Hz M = 1- 230 V T = 3- 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Portata • Flow											
	HP	KW	A	µF	m	DNM	m³/h	0	5,4	6,3	7,2	8,1	9	10,2	11,4	12,6	13,8	
							l/min	0	90	105	120	135	150	170	190	210	230	

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante radiale • Radial impeller								Prevalenza manometrica totale in metri • Total manometric head in meters											
4M20	6/230	2	1,5	11	40	2	2"	56	51	49	46	43	40	35	29	22	15		
4M30	8/230	3	2,2	15,9	60	2	2"	75	67	64	61	57	52	45	38	29	20		
4M30	9/230	3	2,2	15,9	60	2	2"	84	75	72	68	64	59	52	44	34	24		
4T20	6/230	2	1,5	4,2		2	2"	56	51	49	46	43	40	35	29	22	15		
4TH30	8/230	3	2,2	5,7		2	2"	75	67	64	61	57	52	45	38	29	20		
4TH30	9/230	3	2,2	5,7		2	2"	84	75	72	68	64	59	52	44	34	24		
4T40	11/230	4	3	7,6		2	2"	103	93	90	85	80	74	66	56	45	33		
4T55	14/230	5,5	4	10		3	2"	138	125	120	114	107	99	87	74	59	43		
6TA75	17/230	7,5	5,5	12,8		3	2"	164	150	144	137	128	118	103	88	71	52		
6TA75	20/230	7,5	5,5	12,8		3	2"	190	174	167	160	151	141	124	105	84	62		
6TA10	24/230	10	7,5	16,5		3	2"	234	207	199	190	179	166	147	126	102	77		
6TA10	28/230	10	7,5	16,5		3	2"	273	250	240	228	214	199	176	148	118	88		
6TA125	34/230	12,5	9,2	19,7		3	2"	334	307	294	278	260	241	212	180	144	106		
6TAH15	40/230	15	11	24		3	2"	396	361	345	328	309	288	255	217	176	132		

DNM 3" su richiesta • DNM 3" on request

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4M20	6/230	1142	546	146	30,7
4M30	8/230	1370	702	146	38,7
4M30	9/230	1406	702	146	39,3
4T20	6/230	1092	496	146	28,7
4TH30	8/230	1264	596	146	33,9
4TH30	9/230	1300	596	146	34,5
4T40	11/230	1418	642	146	38,8
4T55	14/230	1586	702	146	43,5
6TA75	17/230	1754	762	146	67,3
6TA75	20/230	1862	762	146	69
6TA10	24/230	2056	812	146	77,3
6TA10	28/230	2200	812	146	79,9
6TA125	34/230	2528	852	146	88,7
6TAH15	40/230	2799	907	146	100,9

