

Elettropompe sommerse per pozzi da 6" (150 mm) 60 Hz

Electric submersible pumps for 6" (150 mm) wells 60 Hz



Caratteristiche tecniche 2 poli 60 Hz • Performance characteristics 2 poles 60 Hz

Portata • Flow

60 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Portata • Flow													
	HP	KW	A	µF	m	DNM	m³/h	0	5,4	6,3	7,2	8,1	9	10,2	11,4	12,6	13,8	15	16,2	
							l/min	0	90	105	120	135	150	170	190	210	230	250	270	

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante radiale • Radial impeller							Prevalenza manometrica totale in metri • Total manometric head in meters													
Model	Portata	HP	KW	A	µF	m	DNM	0	5,4	6,3	7,2	8,1	9	10,2	11,4	12,6	13,8	15	16,2	
4T40	6/230	4	3	7		2	2"	82	77	76	74	70	67	62	57	52	46	39	30	
4T55	8/230	5,5	4	9,4		3	2"	112	106	104	101	96	91	84	78	70	62	52	39	
4T55	9/230	5,5	4	9,4		3	2"	124	117	115	112	106	100	93	85	77	68	57	44	
4T75	11/230	7,5	5,5	12		4	2"	152	144	142	137	130	122	114	104	93	81	69	54	
4T100	14/230	10	7,5	16		4	2"	190	177	175	168	159	150	137	123	110	96	81	64	
6TA125	17/230	12,5	9,2	18,8		3	2"	239	225	222	215	204	194	179	163	145	126	108	85	
6TA125	20/230	12,5	9,2	18,8		3	2"	282	267	264	256	244	231	211	193	172	151	128	100	
6TA20	24/230	20	15	30		3	2"	337	317	314	303	288	274	254	232	209	183	155	120	
6TA20	28/230	20	15	30		3	2"	393	374	371	360	344	328	304	278	250	219	184	140	
6TA25	34/230	25	18,5	37,7		3	2"	481	454	450	435	416	396	367	336	301	261	219	166	
6TA25	40/230	25	18,5	37,7		3	2"	570	538	534	516	494	470	438	403	362	316	267	206	

DNM 3" su richiesta • DNM 3" on request

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4T40	6/230	1238	642	146	35,6
4T55	8/230	1370	702	146	39,9
4T55	9/230	1406	702	146	40,5
4T75	11/230	1568	792	146	46,2
4T100	14/230	1756	872	146	51,8
6TA125	17/230	1844	852	146	76,9
6TA125	20/230	1952	852	146	78,6
6TA20	24/230	2231	987	146	96,4
6TA20	28/230	2375	987	146	99,0
6TA25	34/230	2763	1087	146	114,3
6TA25	40/230	2979	1087	146	119,6

