

Elettropompe sommerse per pozzi da 4" (100 mm)

Electric submersible pumps for 4" (100 mm) wells



Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Flow

| 50 Hz M = 1~ 230 V T = 3~ 400 V | Caratteristiche Nominali Nominal Characteristics | | | | | Cavo Cable | | Portata • Flow | | | | | | | | | | | | | | | | | |
|---------------------------------------|---|----|---|----|---|---------------|------|----------------|---|-----|---|-----|---|------|------|------|-------|---|----|----|-----|-----|-----|-----|-----|
| | HP | KW | A | µF | m | DNM | m³/h | 0 | 3 | 4,5 | 6 | 7,5 | 9 | 10,5 | 11,4 | 14,4 | l/min | 0 | 50 | 75 | 100 | 125 | 150 | 175 | 190 |

Prevalenza manometrica totale in metri • Total manometric head in meters

| Girante semiassiale • Semi-Axial impeller | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--------|-----|-----|------|------|---|-----|-----|-----|-----|-----|-----|-----|------|------|------|---|----|----|-----|-----|-----|-----|-----|-----|--|
| Model | Wells | HP | KW | A | µF | m | DNM | 0 | 3 | 4,5 | 6 | 7,5 | 9 | 10,5 | 11,4 | 14,4 | 0 | 50 | 75 | 100 | 125 | 150 | 175 | 190 | 240 | |
| 4M15 | 5/240 | 1,5 | 1,1 | 8 | 31,5 | 2 | 2" | 33 | 31 | 29 | 27 | 24 | 21 | 17 | 15 | 4 | | | | | | | | | | |
| 4M20 | 8/240 | 2 | 1,5 | 11 | 40 | 2 | 2" | 51 | 49 | 47 | 43 | 39 | 34 | 28 | 23 | 7 | | | | | | | | | | |
| 4M30 | 12/240 | 3 | 2,2 | 15,9 | 60 | 2 | 2" | 77 | 73 | 69 | 64 | 58 | 51 | 42 | 35 | 10 | | | | | | | | | | |
| 4T15 | 5/240 | 1,5 | 1,1 | 3,2 | | 2 | 2" | 33 | 31 | 29 | 27 | 24 | 21 | 17 | 15 | 4 | | | | | | | | | | |
| 4T20 | 8/240 | 2 | 1,5 | 4,2 | | 2 | 2" | 51 | 49 | 47 | 43 | 39 | 34 | 28 | 23 | 7 | | | | | | | | | | |
| 4T30 | 12/240 | 3 | 2,2 | 5,7 | | 2 | 2" | 77 | 73 | 69 | 64 | 58 | 51 | 42 | 35 | 10 | | | | | | | | | | |
| 4T40 | 16/240 | 4 | 3 | 7,6 | | 2 | 2" | 110 | 107 | 103 | 96 | 87 | 76 | 60 | 50 | 16 | | | | | | | | | | |
| 4T55 | 20/240 | 5,5 | 4 | 10 | | 3 | 2" | 137 | 134 | 128 | 120 | 109 | 94 | 75 | 63 | 21 | | | | | | | | | | |
| 4T75 | 28/240 | 7,5 | 5,5 | 12,5 | | 4 | 2" | 192 | 187 | 178 | 169 | 154 | 132 | 105 | 88 | 29 | | | | | | | | | | |
| 4T100 | 36/240 | 10 | 7,5 | 16,7 | | 4 | 2" | 247 | 240 | 232 | 218 | 198 | 170 | 135 | 113 | 37 | | | | | | | | | | |

| Tipo Type | | Misure mm Dimensions mm | | | Peso Weight Kg |
|--------------|--------|----------------------------|-----|----|----------------------|
| | | A | B | C | |
| 4M15 | 5/240 | 846 | 471 | 95 | 16 |
| 4M20 | 8/240 | 1031 | 521 | 95 | 18,8 |
| 4M30 | 12/240 | 1367 | 677 | 95 | 27 |
| 4T15 | 5/240 | 816 | 441 | 95 | 14,7 |
| 4T20 | 8/240 | 981 | 471 | 95 | 16,8 |
| 4T30 | 12/240 | 1211 | 521 | 95 | 20,5 |
| 4T40 | 16/240 | 1487 | 617 | 95 | 26,5 |
| 4T55 | 20/240 | 1771 | 677 | 95 | 31,2 |
| 4T75 | 28/240 | 2221 | 767 | 95 | 38,9 |
| 4T100 | 36/240 | 2661 | 847 | 95 | 45,5 |

