

# Elettropompe sommerse per pozzi da 4" (100 mm)

## Electric submersible pumps for 4" (100 mm) wells



Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Flow

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Portata • Flow																		
	HP	KW	A	µF	m	DNM	m³/h	0	3	4,5	6	7,5	9	10,5	11,4	14,4	l/min	0	50	75	100	125	150	175	190

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante semiassiale • Semi-Axial impeller																										
Model	Wells	HP	KW	A	µF	m	DNM	0	3	4,5	6	7,5	9	10,5	11,4	14,4	0	50	75	100	125	150	175	190	240	
4M15	5/240	1,5	1,1	8	31,5	2	2"	33	31	29	27	24	21	17	15	4										
4M20	8/240	2	1,5	11	40	2	2"	51	49	47	43	39	34	28	23	7										
4M30	12/240	3	2,2	15,9	60	2	2"	77	73	69	64	58	51	42	35	10										
4T15	5/240	1,5	1,1	3,2		2	2"	33	31	29	27	24	21	17	15	4										
4T20	8/240	2	1,5	4,2		2	2"	51	49	47	43	39	34	28	23	7										
4T30	12/240	3	2,2	5,7		2	2"	77	73	69	64	58	51	42	35	10										
4T40	16/240	4	3	7,6		2	2"	110	107	103	96	87	76	60	50	16										
4T55	20/240	5,5	4	10		3	2"	137	134	128	120	109	94	75	63	21										
4T75	28/240	7,5	5,5	12,5		4	2"	192	187	178	169	154	132	105	88	29										
4T100	36/240	10	7,5	16,7		4	2"	247	240	232	218	198	170	135	113	37										

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4M15	5/240	846	471	95	16
4M20	8/240	1031	521	95	18,8
4M30	12/240	1367	677	95	27
4T15	5/240	816	441	95	14,7
4T20	8/240	981	471	95	16,8
4T30	12/240	1211	521	95	20,5
4T40	16/240	1487	617	95	26,5
4T55	20/240	1771	677	95	31,2
4T75	28/240	2221	767	95	38,9
4T100	36/240	2661	847	95	45,5

