

Elettropompe sommerse per pozzi da 4" (100 mm) 60 Hz

Electric submersible pumps for 4" (100 mm) wells 60 Hz

Caratteristiche tecniche 2 poli 60 Hz • Performance characteristics 2 poles 60 Hz

60 Hz M = 1~ 230 V T = 3~ 400 V		Caratteristiche Nominali Nominal Characteristics HP KW A µF		Cavo Cable m DNM		P o r t a t a • F l o w											
						m³/h	0	3	4,5	6	7,5	9	10,5	11,4	14,4	18	
						l/min	0	50	75	100	125	150	175	190	240	300	
						P r e v a l e n z a m a n o m e t r i c a t o t a l e i n m e t r i • T o t a l m a n o m e t r i c h e a d i n m e t e r s											
Girante semiassiale • Semi-Axial impeller																	
4M30	5/240	3	2,2	15,2	50	2	2"	50	49	48	47	45	42	37	34	24	8
4TH30	5/240	3	2,2	5,4		2	2"	50	49	48	47	45	42	37	34	24	8
4T40	8/240	4	3	7		2	2"	83	82	80	76	72	66	60	55	39	11
4T55	12/240	5,5	4	9,4		3	2"	118	115	112	107	102	95	86	79	51	15
4T75	16/240	7,5	5,5	12		4	2"	157	154	148	142	133	122	108	98	65	18
4T100	20/240	10	7,5	16		4	2"	195	192	186	179	168	155	139	128	83	23

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4M30	5/240	1052	677	95	24,7
4TH30	5/240	946	571	95	19,6
4T40	8/240	1127	617	95	23,7
4T55	12/240	1367	677	95	28,2
4T75	16/240	1637	767	95	33,9
4T100	20/240	1941	847	95	39,3

