

# Elettropompe sommerse per pozzi da 8" - 12" (200 - 300 mm)

## Electric submersible pumps for 8" - 12" (200 - 300 mm) wells



Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

P o r t a t a • F l o w

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Portata • Flow																		
	HP	KW	A	µF	m	DNM	m³/h	0	60	72	84	90	96	108	120	138	l/min	0	1000	1200	1400	1500	1600	1800	2000

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante semiassiale • Semi-Axial impeller																											
6TA10	1/2500	10	7,5	16,5	3	5"	28	23,5	23	22	21	20	18	15,5	10												
6TA20	2/2500	20	15	31,5	3	5"	56	47	45	43	41,5	40	35,5	31	20												
6TA30	3/2500	30	22	47,3	3	5"	84	70	67,5	64	61	58	52	46	30												
6TA35	4/2500	35	26	54	3	5"	108	92	88	83,5	80	76,5	68	58	36												
6TA40	5/2500	40	30	61,6	3	5"	127	110	105	98	93	88	76,5	63	32												
8TA50	6/2500	50	37	71,5	3,5	5"	153	132	125	117	112	106	93	75	38												
8TA60	7/2500	60	45	85,9	3,5	5"	184	157	150	140	135	129	115	95	51												
8TA75	8/2500	75	55	106	3,5	5"	224	187	180	171	165	158	142	123	81												

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
6TA10	1/2500	1269	967	200	85,5
6TA20	2/2500	1594	1142	200	117,5
6TA30	3/2500	1974	1372	200	153,5
6TA35	4/2500	2358	1618	200	192,5
6TA40	5/2500	2414	1524	200	193,5
8TA50	6/2500	2413	1373	200	255,5
8TA60	7/2500	2643	1453	200	283
8TA75	8/2500	2893	1553	200	316,5

