

Elettropompe sommerse per pozzi da 6" (150 mm)

Electric submersible pumps for 6" (150 mm) wells

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Flow

| 50 Hz M = 1- 230 V T = 3- 400 V | Caratteristiche Nominali Nominal Characteristics | | | | Cavo Cable | | Portata • Flow | | | | | | | | | | | |
|---------------------------------------|---|----|---|----|---------------|-----|----------------|---|-----|------|------|------|------|------|------|------|-----|------|
| | HP | KW | A | µF | m | DNM | m³/h | 0 | 9 | 10,2 | 11,4 | 12,6 | 13,8 | 14,7 | 15,6 | 16,8 | 18 | 19,8 |
| | | | | | | | l/min | 0 | 150 | 170 | 190 | 210 | 230 | 245 | 260 | 280 | 300 | 330 |

Prevalenza manometrica totale in metri • Total manometric head in meters

| Girante radiale • Radial impeller | | | | | | | | Prevalenza manometrica totale in metri • Total manometric head in meters | | | | | | | | | | |
|-----------------------------------|--------|------|------|------|----|---|----|--|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 4M20 | 4/330 | 2 | 1,5 | 11 | 40 | 2 | 2" | 39 | 33,5 | 32 | 30 | 28 | 26 | 24 | 22 | 19 | 16 | 11 |
| 4M30 | 5/330 | 3 | 2,2 | 15,9 | 60 | 2 | 2" | 49 | 42 | 40 | 38 | 35 | 32 | 30 | 27 | 24 | 20 | 14 |
| 4M30 | 6/330 | 3 | 2,2 | 15,9 | 60 | 2 | 2" | 58 | 48 | 46 | 44 | 41 | 38 | 35 | 32 | 28 | 23 | 16 |
| 4T20 | 4/330 | 2 | 1,5 | 4,2 | | 2 | 2" | 39 | 33,5 | 32 | 30 | 28 | 26 | 24 | 22 | 19 | 16 | 11 |
| 4T30 | 5/330 | 3 | 2,2 | 5,7 | | 2 | 2" | 49 | 42 | 40 | 38 | 35 | 32 | 30 | 27 | 24 | 20 | 14 |
| 4T30 | 6/330 | 3 | 2,2 | 5,7 | | 2 | 2" | 58 | 48 | 46 | 44 | 41 | 38 | 35 | 32 | 28 | 23 | 16 |
| 4T40 | 7/330 | 4 | 3 | 7,6 | | 2 | 2" | 68 | 57 | 55 | 52 | 49 | 45 | 42 | 39 | 34 | 29 | 20 |
| 4T55 | 9/330 | 5,5 | 4 | 10 | | 3 | 2" | 89 | 74 | 71 | 66 | 62 | 56 | 52 | 47 | 41 | 34 | 24 |
| 4T55 | 10/330 | 5,5 | 4 | 10 | | 3 | 2" | 102 | 86 | 82 | 77 | 72 | 66 | 62 | 57 | 50 | 42 | 29 |
| 6TA75 | 12/330 | 7,5 | 5,5 | 12,8 | | 3 | 2" | 121 | 101 | 96 | 90 | 84 | 77 | 71 | 65 | 57 | 48 | 33 |
| 6TA75 | 14/330 | 7,5 | 5,5 | 12,8 | | 3 | 2" | 138 | 116 | 110 | 103 | 96 | 88 | 82 | 75 | 65 | 54 | 37 |
| 6TA10 | 16/330 | 10 | 7,5 | 16,5 | | 3 | 2" | 160 | 134 | 127 | 120 | 112 | 104 | 97 | 89 | 78 | 65 | 46 |
| 6TA10 | 19/330 | 10 | 7,5 | 16,5 | | 3 | 2" | 190 | 160 | 153 | 144 | 135 | 125 | 116 | 107 | 94 | 80 | 56 |
| 6TA125 | 23/330 | 12,5 | 9,2 | 19,7 | | 3 | 2" | 233 | 198 | 190 | 180 | 169 | 157 | 147 | 135 | 119 | 101 | 72 |
| 6TA15 | 28/330 | 15 | 11 | 24 | | 3 | 2" | 287 | 247 | 236 | 224 | 211 | 196 | 183 | 170 | 150 | 128 | 93 |
| 6TA20 | 32/330 | 20 | 15 | 31,5 | | 3 | 2" | 326 | 285 | 274 | 260 | 244 | 226 | 210 | 194 | 172 | 148 | 108 |
| 6TA20 | 36/330 | 20 | 15 | 31,5 | | 3 | 2" | 374 | 323 | 311 | 296 | 278 | 256 | 238 | 220 | 194 | 167 | 123 |
| 6TA25 | 43/330 | 25 | 18,5 | 38 | | 3 | 2" | 444 | 383 | 367 | 350 | 328 | 304 | 283 | 262 | 231 | 198 | 145 |

DNM 3" su richiesta • DNM 3" on request

| Tipo Type | | Misure mm Dimensions mm | | | Peso Weight Kg |
|--------------|--------|----------------------------|------|-----|----------------------|
| | | A | B | C | |
| 4M20 | 4/330 | 1070 | 546 | 146 | 28,7 |
| 4M30 | 5/330 | 1262 | 702 | 146 | 36,1 |
| 4M30 | 6/330 | 1298 | 702 | 146 | 36,7 |
| 4T20 | 4/330 | 1020 | 496 | 146 | 26,7 |
| 4T30 | 5/330 | 1106 | 546 | 146 | 29,6 |
| 4T30 | 6/330 | 1142 | 546 | 146 | 30,2 |
| 4T40 | 7/330 | 1274 | 642 | 146 | 35,9 |
| 4T55 | 9/330 | 1406 | 702 | 146 | 40,4 |
| 4T55 | 10/330 | 1442 | 702 | 146 | 40,8 |
| 6TA75 | 12/330 | 1574 | 762 | 146 | 63,3 |
| 6TA75 | 14/330 | 1646 | 762 | 146 | 64,4 |
| 6TA10 | 16/330 | 1768 | 812 | 146 | 71,2 |
| 6TA10 | 19/330 | 1876 | 812 | 146 | 72,5 |
| 6TA125 | 23/330 | 2060 | 852 | 146 | 81 |
| 6TA15 | 28/330 | 2295 | 907 | 146 | 89,6 |
| 6TA20 | 32/330 | 2591 | 987 | 146 | 101,9 |
| 6TA20 | 36/330 | 2735 | 987 | 146 | 106 |
| 6TA25 | 43/330 | 3087 | 1087 | 146 | 121,4 |

