

# Elettropompe sommerse per pozzi da 6" (150 mm) 60 Hz

## Electric submersible pumps for 6" (150 mm) wells 60 Hz

Caratteristiche tecniche 2 poli 60 Hz • Performance characteristics 2 poles 60 Hz

Portata • Flow

60 Hz M = 1- 230 V T = 3- 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable m	DNM	Portata • Flow															
	HP	KW	A	µF			m <sup>3</sup> /h	0	9	10,2	11,4	12,6	13,8	14,7	15,6	16,8	18	19,8	21,6	23,4		
							l/min	0	150	170	190	210	230	245	260	280	300	330	360	390		

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante radiale • Radial impeller							Prevalenza manometrica totale in metri • Total manometric head in meters															
Model	Portata	HP	KW	A	µF	Cavo	0	9	10,2	11,4	12,6	13,8	14,7	15,6	16,8	18	19,8	21,6	23,4			
4T40	4/330	4	3	7		2 2"	58	51	50	48	46	44	42	40	38	35	31	26	20			
4T55	5/330	5,5	4	9,4		3 2"	73	65	62	60	58	56	54	52	49	46	40	33	25			
4T55	6/330	5,5	4	9,4		3 2"	87	73	71	68	66	64	62	60	57	53	46	38	30			
4T75	7/330	7,5	5,5	12		4 2"	100	87	84	82	79	76	73	70	66	62	54	45	35			
4T100	9/330	10	7,5	16		4 2"	130	112	108	104	100	96	93	89	83	77	69	55	43			
4T100	10/330	10	7,5	16		4 2"	146	125	121	117	112	107	103	98	91	85	74	61	48			
6TA125	12/330	12,5	9,2	18,8		3 2"	174	153	148	142	136	129	124	118	109	100	86	70	55			
6TA125	14/330	12,5	9,2	18,8		3 2"	200	168	163	158	151	144	138	132	122	113	97	81	65			
6TA20	16/330	20	15	30		3 2"	230	203	197	189	181	173	166	159	148	137	118	98	76			
6TA20	19/330	20	15	30		3 2"	274	243	236	225	216	206	199	191	179	164	140	114	88			
6TA25	23/330	25	18,5	37,7		3 2"	336	300	290	280	269	258	248	237	222	205	176	145	111			
6TA25	28/330	25	18,5	37,7		3 2"	397	353	344	332	318	302	290	275	258	238	206	173	138			
6TA40	32/330	40	30	58,5		3 2"	469	430	417	404	389	373	359	343	320	295	255	212	166			
6TA40	36/330	40	30	58,5		3 2"	539	487	473	458	442	424	409	392	366	338	292	243	190			

DNM 3" su richiesta • DNM 3" on request

Tipo Type	Misura mm Dimensions mm	Peso Weight			
		A	B	C	
4T40	4/330	1166	642	146	33,6
4T55	5/330	1262	702	146	37,3
4T55	6/330	1298	702	146	37,9
4T75	7/330	1424	792	146	43,3
4T100	9/330	1576	872	146	48,7
4T100	10/330	1612	872	146	49,1
6TA125	12/330	1664	852	146	72,9
6TA125	14/330	1736	852	146	74,0
6TA20	16/330	1943	987	146	90,3
6TA20	19/330	2051	987	146	91,6
6TA25	23/330	2295	1087	146	106,6
6TA25	28/330	2475	1087	146	108,7
6TA40	32/330	2961	1357	146	140,5
6TA40	36/330	3105	1357	146	144,6

