

# Elettropompe sommerse per pozzi da 8" - 12" (200 - 300 mm)

## Electric submersible pumps for 8" - 12" (200 - 300 mm) wells



Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

P o r t a t a • F l o w

50 Hz M = 1- 230 V T = 3- 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Portata • Flow										
	HP	KW	A	µF	m	DNM	m³/h	0	60	75	90	105	120	135	150	180	210
							l/min	0	1000	1250	1500	1750	2000	2250	2500	3000	3500

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante semiassiale • Semi-Axial impeller																		
6TA125	1/3500	12,5	9,2	19,7	3	5"	27	22,5	22	21,5	20,5	19,5	18,5	17	13	8		
6TA20	2C/3500	20	15	31,5	3	5"	48	38	37,5	36,5	35	32,5	30	26,5	16,5			
6TA25	2/3500	25	18,5	38	3	5"	54	45	44	43	41,5	39,5	37	33,5	26	16		
6TA30	3C/3500	30	22	47,3	3	5"	72,5	57,5	56,5	55	52,5	49,5	45	39,5	25			
6TA35	3B/3500	35	26	54	3	5"	78	64	62,5	61	58,5	55,5	52	47,5	35	17,5		
6TA40	3/3500	40	30	61,6	3	5"	81	68	66,5	64,5	62	59	55	50,5	39	23,5		
8TA50	4A/3500	50	37	71,5	3,5	5"	106	89	87	84	80,5	76	71	65,5	50	28		
8TA60	5/3500	60	45	85,9	3,5	5"	130	105,5	104	101	97	92	87	79	58	29		
8TA75	6/3500	75	55	106	3,5	5"	158	134	130,5	126	121	115	107	98,5	75	42		

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
6TA125	1/3500	1309	1007	200	89,5
6TA20	2C/3500	1594	1154	200	117,5
6TA25	2/3500	1694	1242	200	127,5
6TA30	3C/3500	1974	1384	200	153,5
6TA35	3B/3500	2208	1618	200	180
6TA40	3/3500	2114	1524	200	168,5
8TA50	4A/3500	2113	1373	200	230,5
8TA60	5/3500	2343	1453	200	258
8TA75	6/3500	2593	1553	200	291,5

