

Elettropompe sommerse per pozzi da 8" - 12" (200 - 300 mm)

Electric submersible pumps for 8" - 12" (200 - 300 mm) wells

/3750 /4000 

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

P o r t a t a • F l o w

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Portata • Flow												
	HP	KW	A	µF	m	DNM	m³/h	0	60	75	90	105	120	135	150	180	210	225	240
							l/min	0	1000	1250	1500	1750	2000	2250	2500	3000	3500	3750	4000

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante semiassiale • Semi-Axial impeller																						
8TA25	1C/3750	25	18,5	36,6	3,5	6"	46	41,5	40	38,5	37	36	34	32,5	28	23	20	16				
8TA30	1/3750	30	22	44,5	3,5	6"	50	45	43,5	42	40,5	39	37,5	36	33	29	26	23				
8TA40	2C/3750	40	30	58,6	3,5	6"	78	72,5	70	68	65	62	59	55,5	46	34	27					
8TA50	2/3750	50	37	71,5	3,5	6"	92	83	80	77	74	71	68	65	57	46	39	32				
8TA60	2/4000	60	45	85,9	3,5	6"	100	90,5	88	85	82	79	76	73	66	57	51	45				
8TA75	3/4000	75	55	106	3,5	6"	138	123	119	115	111	107	102	97	85	69	59	48				

Tipo Type	Misure mm Dimensions mm			Peso Weight Kg	
	A	B	C		
8TA25	1C/3750	1581	1056	262	175
8TA30	1/3750	1631	1106	262	183
8TA40	2C/3750	1916	1341	262	223,5
8TA50	2/3750	2036	1461	262	243,5
8TA60	2/4000	2116	1541	262	258,5
8TA75	3/4000	2401	1641	262	304

