

# Elettropompe sommerse per pozzi da 6" (150 mm) 60 Hz

## Electric submersible pumps for 6" (150 mm) wells 60 Hz



Caratteristiche tecniche 2 poli 60 Hz • Performance characteristics 2 poles 60 Hz

Portata • Flow

60 Hz M = 1- 230 V T = 3- 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Portata • Flow											
	HP	KW	A	µF	m	DNM	m³/h	0	11,4	13,8	15,6	18	19,8	21,6	24	27	30	31,8
							l/min	0	190	230	260	300	330	360	400	450	500	530

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante radiale • Radial impeller							Prevalenza manometrica totale in metri • Total manometric head in meters										
4T75	4/400	7,5	5,5	12	4	3"	74	64	61	58	54	50	47	41	33	24	19
4T100	5/400	10	7,5	16	4	3"	94	80	76	73	68	64	59	53	44	34	27
4T100	6/400	10	7,5	16	4	3"	110	96	92	89	82	77	72	65	55	44	37
6TA125	7/400	12,5	9,2	18,8	3	3"	133	113	107	103	96	91	85	77	65	53	46
6TA20	8/400	20	15	30	3	3"	151	130	124	119	112	106	100	91	78	64	55
6TA25	10/400	25	18,5	37,7	3	3"	187	159	152	145	136	128	120	109	94	78	66
6TA25	12/400	25	18,5	37,7	3	3"	219	194	186	179	168	159	149	136	116	94	79
6TA30	15/400	30	22	44	3	3"	285	249	239	230	217	206	194	176	152	124	105
6TA40	20/400	40	30	58,5	3	3"	366	315	302	291	275	262	248	226	196	161	139

Tipo Type	Misura mm Dimensions mm	Peso Weight			
		A	B	C	
4T75	4/400	1307	792	146	46,4
4T100	5/400	1437	872	146	52,3
4T100	6/400	1487	872	146	53,7
6TA125	7/400	1517	852	146	77,4
6TA20	8/400	1702	987	146	94,1
6TA25	10/400	1902	1087	146	107,7
6TA25	12/400	2002	1087	146	111,1
6TA30	15/400	2282	1217	146	129,2
6TA40	20/400	2672	1357	146	154,9

