

Elettropompe sommerse per pozzi da 4" (100 mm)

Electric submersible pumps for 4" (100 mm) wells



Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

P o r t a t a • F l o w

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		P o r t a t a • F l o w												
	HP	KW	A	µF	m	DNM	m³/h	0	3	4,5	6	7,5	9	10,5	11,4	14,4	18	21	24
							l/min	0	50	75	100	125	150	175	190	240	300	350	400

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante semiassiale • Semi-Axial impeller																				
4M20	7/420	2	1,5	11	40	2	2"	42	39	37,5	36	34	32	30	29	25	19	13	5	
4M30	10/420	3	2,2	15,9	60	2	2"	58	55	53	51	49	46	43	41	35	26	17	6	
4T20	7/420	2	1,5	4,2		2	2"	42	39	37,5	36	34	32	30	29	25	19	13	5	
4T30	10/420	3	2,2	5,7		2	2"	58	55	53	51	49	46	43	41	35	26	17	6	
4T40	14/420	4	3	7,6		2	2"	87	79	75	71	67	63	59	57	48	35	21	7	
4T55	17/420	5,5	4	10		3	2"	97	91	89	85	80	74	69	65	55	39	25	10	
4T55	19/420	5,5	4	10		3	2"	110	103	99	95	90	84	78	75	62	44	28	11	
4T75	26/420	7,5	5,5	12,5		4	2"	147	137	132	126	119	112	104	99	83	60	38	13	
4T100	34/420	10	7,5	16,7		4	2"	191	176	170	161	152	143	132	126	104	75	46	16	

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4M20	7/420	1276	536	96	20
4M30	10/420	1667	692	96	28,4
4T20	7/420	1226	486	96	18
4T30	10/420	1511	536	96	21,9
4T40	14/420	1987	632	96	29,4
4T55	17/420	2277	692	96	34,1
4T55	19/420	2437	692	96	35,4
4T75	26/420	3137	782	96	44,3
4T100	34/420	3912	862	96	52,6

