

Elettropompe sommerse per pozzi da 4" (100 mm) 60 Hz

Electric submersible pumps for 4" (100 mm) wells 60 Hz



Caratteristiche tecniche 2 poli 60 Hz • Performance characteristics 2 poles 60 Hz

Portata • Flow

60 Hz M = 1- 230 V T = 3- 400 V	Caratteristiche Nominali				Cavo Cable		Portata • Flow													
	HP	KW	A	µF	m	DNM	m³/h	0	3	4,5	6	7,5	9	10,5	11,4	14,4	18	21	25,2	
							l/min	0	50	75	100	125	150	175	190	240	300	350	420	

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante semiassiale • Semi-Axial impeller																				
4T40	7/420	4	3	7	2	2"	58	55	53	51	49	47	44	43	37	28	21	11		
4T55	10/420	5,5	4	9,4	3	2"	83	79	77	74	71	68	64	62	52	40	30	16		
4T75	14/420	7,5	5,5	12	4	2"	115	108	104	100	96	91	86	83	71	56	43	24		
4T100	17/420	10	7,5	16	4	2"	140	132	127	122	117	111	106	102	89	72	57	35		
4T100	19/420	10	7,5	16	4	2"	155	147	143	138	133	127	121	118	105	87	72	48		

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4T40	7/420	1372	632	96	24,9
4T55	10/420	1667	692	96	29,6
4T75	14/420	2137	782	96	36,8
4T100	17/420	2447	862	96	42,4
4T100	19/420	2607	862	96	43,7

