

Elettropompe sommerse per pozzi da 6" (150 mm)

Electric submersible pumps for 6" (150 mm) wells



Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

P o r t a t a • F l o w

50 Hz M = 1- 230 V T = 3- 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		P o r t a t a • F l o w																						
	HP	KW	A	µF	m	DNM	m³/h	0	11,4	13,8	15,6	18	19,8	21,6	24	27	30	33	l/min	0	190	230	260	300	330	360	400	450	500

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante radiale • Radial impeller																										
4T40	4/530	4	3	7,6	2	3"	40	36	35	34	33	32	30	27	22	16	10									
4T55	6/530	5,5	4	10	3	3"	60	53	52	51	49	48	45	40	33	24	16									
6TA75	8/530	7,5	5,5	12,8	3	3"	80	70	69	67	65	64	61	53	43	33	21									
6TA10	11/530	10	7,5	16,5	3	3"	110	97	95	93	90	87	83	73	60	44	29									
6TA125	14/530	12,5	9,2	19,7	3	3"	139	123	120	118	114	111	106	94	76	56	37									
6TA15	17/530	15	11	24	3	3"	169	149	146	143	139	135	129	113	93	69	45									
6TA20	22/530	20	15	31,5	3	3"	219	193	189	184	179	175	167	147	120	89	59									
6TA25	28/530	25	18,5	38	3	3"	279	246	240	235	228	223	213	187	152	113	75									
6TA30	33/530	30	22	47,3	3	3"	328	290	283	277	269	263	251	221	180	133	88									

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4T40	4/530	1241	642	146	35,7
4T55	6/530	1401	702	146	40,1
6TA75	8/530	1579	762	146	62,6
6TA10	11/530	1761	812	146	70,0
6TA125	14/530	1951	852	146	76,9
6TA15	17/530	2156	907	146	85,3
6TA20	22/530	2486	987	146	89,9
6TA25	28/530	2958	1087	146	115,3
6TA30	33/530	3338	1217	146	133,3

