

Elettropompe sommerse per pozzi da 6" (150 mm) 60 Hz

Electric submersible pumps for 6" (150 mm) wells 60 Hz



Caratteristiche tecniche 2 poli 60 Hz • Performance characteristics 2 poles 60 Hz

60 Hz M = 1- 230 V T = 3- 400 V		Caratteristiche Nominali Nominal Characteristics HP KW A μ F		Cavo Cable m DNM		P o r t a t a • F l o w													
						Prevalenza manometrica totale in metri • Total manometric head in meters													
						m ³ /h	0	11,4	13,8	15,6	18	19,8	21,6	24	27	30	33	36	39
						l/min	0	190	230	260	300	330	360	400	450	500	550	600	650
Girante radiale • Radial impeller																			
4T75	4/530	7,5	5,5	12	4	3"	58	53	52	51	50	48	46	42	37	30	23	16	8
4T100	6/530	10	7,5	16	4	3"	87	79	77	75	72	70	67	63	57	49	40	30	18
6TA125	8/530	12,5	9,2	18,8	3	3"	115	103	100	98	95	92	89	84	75	65	53	39	25
6TA20	11/530	20	15	30	3	3"	156	143	140	137	132	128	122	114	101	87	70	50	31
6TA25	14/530	25	18,5	37,7	3	3"	200	182	177	172	166	161	154	143	128	109	89	65	39
6TA30	17/530	30	22	44	3	3"	237	214	206	200	191	184	177	167	153	134	111	82	49
6TA40	22/530	40	30	58,5	3	3"	315	284	276	269	259	250	240	224	199	170	136	99	60

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4T75	4/530	1391	792	146	43,1
4T100	6/530	1571	872	146	48,4
6TA125	8/530	1669	852	146	72,1
6TA20	11/530	1936	987	146	89,5
6TA25	14/530	2186	1087	146	102,4
6TA30	17/530	2466	1217	146	118,3
6TA40	22/530	2856	1357	146	137,9

