

# Elettropompe sommerse per pozzi da 4" (100 mm)

## Electric submersible pumps for 4" (100 mm) wells

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

### Portata • Flow

50 Hz M = 1- 230 V T = 3- 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Portata • Flow								
	HP	KW	A	µF	m	DNM	m³/h	0	0,6	1,2	1,5	1,8	2,4	3	3,3
							l/min	0	10	20	25	30	40	50	55

### Prevalenza manometrica totale in metri • Total manometric head in meters

#### Girante radiale • Radial impeller

Model	Flow (m³/h)	HP	KW	A	µF	m	DNM	0	10	20	25	30	40	50	55
4M05 7/55	7	0,5	0,37	3,6	20	2	1"½	35	33	31	29	27	20	10	5
4M05 11/55	11	0,5	0,37	3,6	20	2	1"½	53	51	47	44	41	31	18	11
4M075 15/55	15	0,75	0,55	4,4	20	2	1"½	78	76	71	67	62	49	32	22
4M10 19/55	19	1	0,75	6	25	2	1"½	101	98	92	87	82	65	43	31
4M15 28/55	28	1,5	1,1	8	31,5	2	1"½	144	139	130	124	115	91	60	43
4M20 37/55	37	2	1,5	11	40	2	1"½	194	189	178	169	158	127	85	60
4T05 7/55	7	0,5	0,37	1,8		2	1"½	35	33	31	29	27	20	10	5
4T05 11/55	11	0,5	0,37	1,8		2	1"½	53	51	47	44	41	31	18	11
4T075 15/55	15	0,75	0,55	2		2	1"½	78	76	71	67	62	49	32	22
4T10 19/55	19	1	0,75	2,3		2	1"½	101	98	92	87	82	65	43	31
4T15 28/55	28	1,5	1,1	3,2		2	1"½	144	139	130	124	115	91	60	43
4T20 37/55	37	2	1,5	4,2		2	1"½	194	189	178	169	158	127	85	60

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4M05	7/55	728	406	95	12,1
4M05	11/55	828	406	95	12,8
4M075	15/55	928	406	95	13,4
4M10	19/55	1058	436	95	15,6
4M15	28/55	1363	466	95	18,9
4M20	37/55	1638	516	95	21,9
4T05	7/55	728	406	95	12,2
4T05	11/55	828	406	95	12,9
4T075	15/55	928	406	95	13,5
4T10	19/55	1028	406	95	14,2
4T15	28/55	1333	436	95	17,6
4T20	37/55	1588	466	95	19,9

