

# Elettropompe sommerse per pozzi da 8" - 12" (200 - 300 mm)

Electric submersible pumps for 8" - 12" (200 - 300 mm) wells

/5000-/6000 

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

P o r t a t a • F l o w

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		P o r t a t a • F l o w												
	HP	KW	A	µF	m	DNM	m³/h	0	90	105	120	135	150	180	210	225	240	300	330
							l/min	0	1500	1750	2000	2250	2500	3000	3500	3750	4000	5000	5500

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante semiassiale • Semi-Axial impeller																				
8TA25	1/5000	25	18,5	36,6	3,5	6"	35	31,5	30,5	30	29	28	26,5	24	22,5	21	13	8,5		
8TA30	1/5200	30	22	44,5	3,5	6"	43	38	37	36	35	34	32	30	28,5	27	20	16		
8TA40	1/6000	40	30	58,6	3,5	6"	46	42	41	40	39	38	36	33	32	31	24	20		
8TA50	2/5000	50	37	71,5	3,5	6"	70	63,5	62	60,5	59	57	52	48	45	42	27	17		
8TA60	2/5200	60	45	85,9	3,5	6"	86	78	76	74	72	70,5	66	61	58,5	55	42	34		
8TA75	2/6000	75	55	106	3,5	6"	92	83	81,5	80	78	76	72	67	64,5	62	49	40		

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
8TA25	1/5000	1581	1056	262	175
8TA30	1/5200	1631	1106	262	183
8TA40	1/6000	1731	1206	262	199
8TA50	2/5000	2036	1461	262	243,5
8TA60	2/5200	2116	1541	262	258,5
8TA75	2/6000	2216	1641	262	279,5

