

# Elettropompe sommerse per pozzi da 6" (150 mm)

## Electric submersible pumps for 6" (150 mm) wells



Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Flow

50 Hz M = 1- 230 V T = 3- 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Portata • Flow											
	HP	KW	A	µF	m	DNM	m³/h	0	18	19,8	21,6	24	27	30	33	36	39	42
							l/min	0	300	330	360	400	450	500	550	600	650	700

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante semiassiale • Semi-Axial impeller																	
4T55	3/700	5,5	4	10	3	3"	41	35	34	33	31	28	25	22	18	14	9
6TA75	5/700	7,5	5,5	12,8	3	3"	68	59	57	55	51	46	41	35	28	21	14
6TA10	6/700	10	7,5	16,5	3	3"	84	68	66	63	59	54	48	42	34	27	17
6TA125	8/700	12,5	9,2	19,7	3	3"	113	93	91	87	83	76	69	60	50	40	29
6TA15	10/700	15	11	24	3	3"	141	116	114	110	104	96	86	75	62	50	36
6TA20	13/700	20	15	31,5	3	3"	183	152	148	144	136	125	111	96	80	63	45
6TA25	16/700	25	18,5	38	3	3"	223	186	180	173	164	150	134	116	96	75	54
6TA30	19/700	30	22	47,3	3	3"	270	219	213	206	195	179	159	137	114	89	63

Tipo Type	Misura mm Dimensions mm	Peso Weight			
		A	B	C	
4T55	3/700	1337	702	146	39,7
6TA75	5/700	1553	762	146	63,1
6TA10	6/700	1681	812	146	69,7
6TA125	8/700	1877	852	146	76,2
6TA15	10/700	2088	907	146	85,1
6TA20	13/700	2402	987	146	98,8
6TA25	16/700	2736	1087	146	112,3
6TA30	19/700	3100	1217	146	129,4

