

# Elettropompe sommerse per pozzi da 6" (150 mm) 60 Hz

## Electric submersible pumps for 6" (150 mm) wells 60 Hz



Caratteristiche tecniche 2 poli 60 Hz • Performance characteristics 2 poles 60 Hz

60 Hz M = 1~ 230 V T = 3~ 400 V		Caratteristiche Nominali				Cavo Cable		P o r t a t a • F l o w														
		HP	KW	A	µF	m	DNM	m³/h	0	18	19,8	21,6	24	27	30	33	36	39	42	45	49,5	
								Prevalenza manometrica totale in metri • Total manometric head in meters														
		Girante semiassiale • Semi-Axial impeller																				
4T100	3/700	10	7,5	16	4	3"	62	52	51	50	47	45	41	38	34	30	26	21	12			
6TA125	5/700	12,5	9,2	18,8	3	3"	101	84	81	79	76	72	67	62	56	49	42	34	21			
6TA20	6/700	20	15	30	3	3"	121	103	101	98	94	89	83	76	69	61	53	43	29			
6TA25	8/700	25	18,5	37,7	3	3"	163	140	137	134	130	124	117	109	99	84	77	65	46			
6TA25	10/700	25	18,5	37,7	3	3"	195	164	161	158	153	146	139	130	120	108	95	80	58			
6TA40	13/700	40	30	58,5	3	3"	264	229	225	220	213	203	190	176	160	143	124	104	72			

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4T100	3/700	1507	872	146	48,0
6TA125	5/700	1643	852	146	72,7
6TA20	6/700	1856	987	146	88,8
6TA25	8/700	2112	1087	146	101,8
6TA25	10/700	2268	1087	146	104,2
6TA40	13/700	2772	1357	146	137,4

