

Elettropompe sommerse per pozzi da 4" (100 mm)

Electric submersible pumps for 4" (100 mm) wells

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Flow

50 Hz M = 1- 230 V T = 3- 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Portata • Flow												
	HP	KW	A	µF	m	DNM	m³/h	0	1,2	1,5	1,8	2,4	3	3,3	3,6	4,2	4,8	5,4	
							l/min	0	20	25	30	40	50	55	60	70	80	90	
Prevalenza manometrica totale in metri • Total manometric head in meters																			
Girante radiale • Radial impeller																			
4M05	5/90	0,5	0,37	3,6	20	2	1"½	30	29	28	27	26	24	23	22	18	15	10	
4M075	7/90	0,75	0,55	4,4	20	2	1"½	42	40	39	38	37	34	32	30	27	21	16	
4M10	10/90	1	0,75	6	25	2	1"½	60	57	56	55	52	48	46	43	37	30	21	
4M15	13/90	1,5	1,1	8	31,5	2	1"½	78	74	73	71	67	62	59	56	48	39	28	
4M15	15/90	1,5	1,1	8	31,5	2	1"½	89	86	84	82	78	72	69	65	56	45	33	
4M20	19/90	2	1,5	11	40	2	1"½	114	108	106	104	99	92	87	82	71	57	41	
4M30	22/90	3	2,2	15,9	60	2	1"½	134	126	124	121	115	106	101	95	82	65	48	
4M30	25/90	3	2,2	15,9	60	2	1"½	151	142	140	137	130	121	115	108	93	75	54	
4M30	28/90	3	2,2	15,9	60	2	1"½	168	159	156	153	145	135	128	121	104	84	61	
4T05	5/90	0,5	0,37	1,8		2	1"½	30	29	28	27	26	24	23	22	18	15	10	
4T075	7/90	0,75	0,55	2		2	1"½	42	40	39	38	37	34	32	30	27	21	16	
4T10	10/90	1	0,75	2,3		2	1"½	60	57	56	55	52	48	46	43	37	30	21	
4T15	13/90	1,5	1,1	3,2		2	1"½	78	74	73	71	67	62	59	56	48	39	28	
4T15	15/90	1,5	1,1	3,2		2	1"½	89	86	84	82	78	72	69	65	56	45	33	
4T20	19/90	2	1,5	4,2		2	1"½	114	108	106	104	99	92	87	82	71	57	41	
4T30	22/90	3	2,2	5,7		2	1"½	134	126	124	121	115	106	101	95	82	65	48	
4TH30	25/90	3	2,2	5,7		2	1"½	151	142	140	137	130	121	115	108	93	75	54	
4TH30	28/90	3	2,2	5,7		2	1"½	168	159	156	153	145	135	128	121	104	84	61	
4T40	33/90	4	3	7,6		2	1"½	198	188	184	180	171	159	152	143	122	98	71	
4T40	37/90	4	3	7,6		2	1"½	218	211	207	202	192	178	169	160	137	110	80	

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4M05	5/90	678	406	95	11,8
4M075	7/90	728	406	95	12,1
4M10	10/90	833	436	95	14,2
4M15	13/90	938	466	95	16,1
4M15	15/90	988	466	95	16,4
4M20	19/90	1138	516	95	18,8
4M30	22/90	1369	672	95	25,9
4M30	25/90	1444	672	95	26,4
4M30	28/90	1569	672	95	27,2
4T05	5/90	678	406	95	11,9
4T075	7/90	728	406	95	12,2
4T10	10/90	803	406	95	12,8
4T15	13/90	908	436	95	14,8
4T15	15/90	958	436	95	15,1
4T20	19/90	1088	466	95	16,8
4T30	22/90	1213	516	95	19,4
4TH30	25/90	1338	566	95	21,6
4TH30	28/90	1463	566	95	22,4
4T40	33/90	1634	612	95	26,4
4T40	37/90	1734	612	95	27

