

Elettropompe sommerse per pozzi da 6" (150 mm)

Electric submersible pumps for 6" (150 mm) wells



Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Flow

50 Hz M = 1- 230 V T = 3- 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Portata • Flow											
	HP	KW	A	µF	m	DNM	m³/h	0	24	27	30	33	36	39	42	48	54	60
							l/min	0	400	450	500	550	600	650	700	800	900	1000

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante semiassiale • Semi-Axial impeller							Prevalenza manometrica totale in metri • Total manometric head in meters											
Model	Flow (m³/h)	HP	KW	A	µF	m	DNM	0	24	27	30	33	36	39	42	48	54	60
4T55	2/900	5,5	4	10	3	3"		29	24	23	22	21	20	19	18	15,5	12,5	9
6TA75	3/900	7,5	5,5	12,8	3	3"		41	37	36	35	33,5	32	30	28	24	19	13
6TA10	4/900	10	7,5	16,5	3	3"		56	50	48	46	44	42	40	38	33	26	18
6TA125	5/900	12,5	9,2	19,7	3	3"		70	63	61	59	56	54	51	48	42	33	23
6TA15	6/900	15	11	24	3	3"		86	76	73,5	71	68	65	62	59	51	41	29
6TA20	8/900	20	15	31,5	3	3"		114	101	98	95	91	87	83	78	68	55	38
6TA25	10/900	25	18,5	38	3	3"		143	127	123	119	114	109	104	98	85	68	48
6TA30	12/900	30	22	47,3	3	3"		170	152	147	142	137	131	125	118	103	83	58
6TA40	15/900	40	30	61,6	3	3"		210	190	183	177	170	163	156	147	127	102	74

Tipo Type	Misura mm Dimensions mm	Peso Weight			
		A	B	C	
4T55	2/900	1323	702	146	38,8
6TA75	3/900	1491	762	146	61,6
6TA10	4/900	1649	812	146	68,9
6TA125	5/900	1797	852	146	74,7
6TA15	6/900	1960	907	146	82,9
6TA20	8/900	2256	987	146	96,4
6TA25	10/900	2572	1087	146	110,1
6TA30	12/900	2918	1217	146	127,3
6TA40	15/900	3382	1357	146	147,9

