

Elettropompe sommerse per pozzi da 6" (150 mm) 60 Hz

Electric submersible pumps for 6" (150 mm) wells 60 Hz



Caratteristiche tecniche 2 poli 60 Hz • Performance characteristics 2 poles 60 Hz

60 Hz M = 1~ 230 V T = 3~ 400 V		Caratteristiche Nominali Nominal Characteristics HP KW A µF		Cavo Cable m DNM		P o r t a t a • F l o w													
						m³/h	0	24	27	30	33	36	39	42	48	54	60	69	78
						l/min	0	400	450	500	550	600	650	700	800	900	1000	1150	1300
						P r e v a l e n z a m a n o m e t r i c a t o t a l e i n m e t r i • T o t a l m a n o m e t r i c h e a d i n m e t e r s													
Girante semiassiale • Semi-Axial impeller																			
4T100	2/900	10	7,5	16	4	3"	41	35	34	32	31	30	29	27	25	21	18	12	5
6TA15	3/900	15	11	22,2	3	3"	59	52	51	50	48	47	45	43	39	34	29	20	9
6TA20	4/900	20	15	30	3	3"	79	73	71	70	68	66	64	61	56	49	42	29	14
6TA25	5/900	25	18,5	37,7	3	3"	100	92	91	89	86	84	81	78	71	63	54	39	21
6TA25	6/900	25	18,5	37,7	3	3"	120	109	107	105	102	99	96	92	84	75	65	48	30
6TA40	8/900	40	30	58,5	3	3"	162	150	146	143	139	135	130	125	115	103	90	68	42

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4T100	2/900	1493	872	146	47,1
6TA15	3/900	1636	907	146	77,2
6TA20	4/900	1824	987	146	88,0
6TA25	5/900	2032	1087	146	100,3
6TA25	6/900	2140	1087	146	102,0
6TA40	8/900	2626	1357	146	135,0

