

Elettropompe sommerse per pozzi da 4" (100 mm) 60 Hz

Electric submersible pumps for 4" (100 mm) wells 60 Hz



Caratteristiche tecniche 2 poli 60 Hz • Performance characteristics 2 poles 60 Hz

Portata • Flow

60 Hz M = 1- 230 V T = 3- 400 V	Caratteristiche Nominali		Nominal Characteristics		Cavo Cable		Portata • Flow													
	HP	KW	A	µF	m	DNM	m³/h	0	1,2	1,5	1,8	2,4	3	3,3	3,6	4,2	4,8	5,4	6,3	
							l/min	0	20	25	30	40	50	55	60	70	80	90	105	

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante radiale • Radial impeller																					
4M10	5/90	1	0,75	6	20	2	1"½	41	40	39	38	37	35	34	33	30	26	22	14		
4M15	7/90	1,5	1,1	8	25	2	1"½	58	56	55	54	52	49	48	46	42	37	31	21		
4M20	10/90	2	1,5	11	35	2	1"½	82	78	77	76	73	69	66	64	58	51	42	28		
4M30	13/90	3	2,2	15,2	50	2	1"½	108	105	103	101	96	90	87	83	75	65	54	35		
4M30	15/90	3	2,2	15,2	50	2	1"½	130	127	125	123	107	110	106	102	91	99	66	44		
4T10	5/90	1	0,75	2,3		2	1"½	41	40	39	38	37	35	34	33	30	26	22	14		
4T15	7/90	1,5	1,1	2,9		2	1"½	58	56	55	54	52	49	48	46	42	37	31	21		
4T20	10/90	2	1,5	3,8		2	1"½	82	78	77	76	73	69	66	64	58	51	42	28		
4TH30	13/90	3	2,2	5,4		2	1"½	108	105	103	101	96	90	87	83	75	65	54	35		
4TH30	15/90	3	2,2	5,4		2	1"½	130	127	125	123	107	110	106	102	91	99	66	44		
4T40	19/90	4	3	7		2	1"½	160	153	150	147	140	132	127	122	110	96	80	53		
4T40	22/90	4	3	7		2	1"½	184	177	174	171	163	153	147	141	128	112	94	62		
4T55	25/90	5,5	4	9,4		3	1"½	208	199	195	192	183	173	167	160	145	127	107	70		
4T55	28/90	5,5	4	9,4		3	1"½	232	223	219	215	206	194	187	180	163	142	120	79		
4T75	33/90	7,5	5,5	12		4	1"½	276	262	257	253	242	230	222	214	195	172	144	94		
4T75	37/90	7,5	5,5	12		4	1"½	310	292	288	282	270	256	249	240	220	196	165	108		

Tipo Type		Misure mm Dimensions mm			Peso Weight Kg
		A	B	C	
4M10	5/90	708	436	95	13,2
4M15	7/90	788	466	95	14,8
4M20	10/90	913	516	95	17,6
4M30	13/90	1144	672	95	24,8
4M30	15/90	1194	672	95	25,1
4T10	5/90	678	406	95	11,9
4T15	7/90	758	436	95	13,4
4T20	10/90	863	466	95	15,3
4TH30	13/90	1038	566	95	19,7
4TH30	15/90	1088	566	95	20,0
4T40	19/90	1234	612	95	23,7
4T40	22/90	1309	612	95	24,1
4T55	25/90	1444	672	95	27,6
4T55	28/90	1569	672	95	28,4
4T75	33/90	1784	762	95	33,6
4T75	37/90	1884	762	95	34,4

