

# Elettropompe sommergibili ad alta prevalenza

## High head electric submersible pumps

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

		P o r t a t a • F l o w											
50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable m	DNM	Passaggio solidi Solids passage ø	Flow					
	HP	KW	A max	µF				m³/h	0	1,2	2,4	3,6	4,8
		Prevalenza manometrica totale in metri • Total manometric head in meters											
Girante aperta • Open impeller													
SEMISOM 130 H M	1,5	1,1	7,6	25	5	1" 1/2	5	30	29	26,5	23,5	19,5	15
SEMISOM 130 H T	1,5	1,1	2,9		5	1" 1/2	5	30	29	26,5	23,5	19,5	15

I modelli monofase sono disponibili con o senza galleggiante • Single-phase electric pumps are available with or without float switch  
 A richiesta dispositivo di discesa ed ancoraggio • Available, on request, descent and anchorage device

Tipo Type		Misure mm Dimensions mm				Peso Weight Kg
		A	B	C	D	
SEMISOM 130 H M		426	69	240	190	21,8
SEMISOM 130 H T		426	69	240	190	21,5

