

Elettropompe esterne verticali multistadio CTV

External vertical multistage electric pumps CTV



Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Flow

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics		Portata • Flow															
	HP	KW	A	μF	DNA	DNM	m³/h	0	11,4	13,8	15,6	18	19,8	21,6	24	27	30	33
							0	190	230	260	300	330	360	400	450	500	550	

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante radiale • Radial impeller		Prevalenza manometrica totale in metri • Total manometric head in meters																
CTV40	4/530	4	3	10,7/6,2	2"½	2"	40	35	34	33	32	30	27	22	16	10		
CTV55	6/530	5,5	4	9,2/5,3	2"½	2"	60	52	51	49	48	45	40	33	24	16		
CTV75	8/530	7,5	5,5	11,2/6,5	2"½	2"	80	69	67	65	64	61	53	43	33	21		
CTV100	11/530	10	7,5	15,7/9,1	2"½	2"	110	95	93	90	87	83	73	60	44	29		
CTV125	14/530	12,5	9,2	18,5/10,7	2"½	2"	139	120	118	114	111	106	94	76	56	37		

Tipo Type	Misura mm Dimensions mm	Peso Weight				
		A	B	C	D	Kg
CTV40	4/530	848	327	200	68	40,2
CTV55	6/530	948	427	200	68	42,7
CTV75	8/530	1069	527	200	68	51,2
CTV100	11/530	1250	677	200	68	63,4
CTV125	14/530	1405	827	200	68	70,7

