

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Capacity

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics						Portata • Capacity							
	HP	KW	A	μF	DNA	DNM	m³/h	0	3,6	4,8	6	8,4	12	14,4
							l/min	0	60	80	100	140	200	240

Prevalenza manometrica totale in metri • Total manometric head in meters

2 elettropompe esterne verticali multistadio • 2 external vertical multistage electric pumps														
G-CMV10	6/110	1-1	0,75-0,75	6,2-6,2	20-20	2"	1"½	54	50	47	44	37	23	11
G-CMV15	9/110	1,5-1,5	1,1-1,1	8-8	30-30	2"	1"½	80	72	69	65	55	33	16
G-CTV10	6/110	1-1	0,75-0,75	1,9-1,9		2"	1"½	54	50	47	44	37	23	11
G-CTV15	9/110	1,5-1,5	1,1-1,1	2,7-2,7		2"	1"½	80	72	69	65	55	33	16
G-CTV20	12/110	2-2	1,5-1,5	3,3-3,3		2"	1"½	105	95	91	85	71	44	21

Tipo Type	Misure mm Dimensions mm	Misura				Peso Weight Kg
		A	B	C	D	
G-CMV10	6/110	712	286	620	600	64,4
G-CMV15	9/110	802	376	620	600	71,6
G-CTV10	6/110	715	286	620	600	62
G-CTV15	9/110	805	376	620	600	69,6
G-CTV20	12/110	909	466	620	600	72,6

