

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Capacity

50 Hz	Caratteristiche Nominali								Performance characteristics										
M = 1~ 230 V	Nominal Characteristics								m ³ /h	0	6	8,4	12	14,4	16,8	19,2	22,8	25,2	27,6
T = 3~ 400 V	HP	KW	A	µF	DNA	DNM													
								0	100	140	200	240	280	320	380	420	460		

Prevalenza manometrica totale in metri • Total manometric head in meters

2 elettropompe esterne verticali multistadio • 2 external vertical multistage electric pumps																			
G-CMV15	5/230	1,5-1,5	1,1-1,1	8-8	30-30	2"	2"	47	46	44	41	39	36	32	25	20	13		
G-CMV20	6/230	2-2	1,5-1,5	10,9-10,9	45-45	2"	2"	56	55	53	50	46	43	37	28	22	15		
G-CMV30	8/230	3-3	2,2-2,2	16,5-16,5	60-60	2"	2"	75	72	69	65	59	55	49	37	29	20		
G-CTV15	5/230	1,5-1,5	1,1-1,1	2,7-2,7		2"	2"	47	46	44	41	39	36	32	25	20	13		
G-CTV20	6/230	2-2	1,5-1,5	3,3-3,3		2"	2"	56	55	53	50	46	43	37	28	22	15		
G-CTV30	8/230	3-3	2,2-2,2	5,3-5,3		2"	2"	75	72	69	65	59	55	49	37	29	20		
G-CTV40	11/230	4-4	3-3	6,8-6,8		2"	2"	103	100	97	91	85	78	70	56	46	33		

Tipo Type	Misura mm Dimensions mm	Misura mm Dimensions mm				Peso Weight Kg
		A	B	C	D	
G-CMV15	5/230	712	286	620	600	69,2
G-CMV20	6/230	765	322	620	600	72,6
G-CMV30	8/230	891	394	620	600	84,4
G-CTV15	5/230	715	286	620	600	67,2
G-CTV20	6/230	765	322	620	600	68,6
G-CTV30	8/230	861	394	620	600	81,4
G-CTV40	11/230	1001	502	620	600	100

