

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Capacity

50 Hz	Caratteristiche Nominali							Portata • Capacity											
M = 1~ 230 V	Nominal Characteristics							m ³ /h	0	12	14,4	16,8	19,2	22,8	25,2	27,6	31,2	36	39,6
T = 3~ 400 V	HP	KW	A	μF	DNA	DNM		l/min	0	200	240	280	320	380	420	460	520	600	660

Prevalenza manometrica totale in metri • Total manometric head in meters

2 elettropompe esterne verticali multistadio • 2 external vertical multistage electric pumps																			
G-CMV30	5/330	3-3	2,2-2,2	16,5-16,5	60-60	3"	2"		49	46	44	43	41	38	35	33	28	20	14
G-CTV30	5/330	3-3	2,2-2,2	5,3-5,3		3"	2"		49	46	44	43	41	38	35	33	28	20	14
G-CTV40	7/330	4-4	3-3	6,8-6,8		3"	2"		68	63	61	58	56	52	49	45	39	29	20
G-CTV55	10/330	5,5-5,5	4-4	8,5-8,5		3"	2"		102	94	91	88	84	77	72	66	57	42	29

Tipo Type	Misure mm Dimensions mm	Misure mm				Peso Weight Kg
		A	B	C	D	
G-CMV30	5/330	783	286	770	600	83,2
G-CTV30	5/330	753	286	770	600	80,2
G-CTV40	7/330	857	358	770	600	96,6
G-CTV55	10/330	965	466	770	600	102

