

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Capacity

| 50 Hz M = 1~ 230 V T = 3~ 400 V | Caratteristiche Nominali Nominal Characteristics | | | | | | Portata • Capacity | | | | | | | | | | | |
|---------------------------------------|---|----|---|----|-----|-----|--------------------|---|-----|------|------|-----|-----|------|------|------|------|------|
| | HP | KW | A | µF | DNA | DNM | m³/h | 0 | 36 | 39,6 | 43,2 | 48 | 54 | 60 | 66 | 72 | 78 | 84 |
| | | | | | | | l/min | 0 | 600 | 660 | 720 | 800 | 900 | 1000 | 1100 | 1200 | 1300 | 1400 |

Prevalenza manometrica totale in metri • Total manometric head in meters

| 2 elettropompe esterne verticali multistadio • 2 external vertical multistage electric pumps | | | | | | | | | | | | | | | | | |
|--|---------------|-----------|---------|-----------|----|----|-----|-----|-----|-----|-----|----|----|----|----|----|----|
| G-CTV75 | 5/700 | 7,5-7,5 | 5,5-5,5 | 13-13 | 4" | 3" | 68 | 59 | 58 | 55 | 51 | 46 | 41 | 35 | 28 | 22 | 14 |
| G-CTV100 | 6/700 | 10-10 | 7,5-7,5 | 16,5-16,5 | 4" | 3" | 84 | 68 | 66 | 63 | 59 | 54 | 48 | 42 | 34 | 27 | 17 |
| G-CTV125 | 8/700 | 12,5-12,5 | 9,2-9,2 | 19,2-19,2 | 4" | 3" | 113 | 93 | 91 | 87 | 83 | 76 | 69 | 60 | 50 | 40 | 29 |
| G-CTV150 | 10/700 | 15-15 | 11-11 | 22,7-22,7 | 4" | 3" | 141 | 116 | 114 | 110 | 104 | 96 | 86 | 75 | 62 | 50 | 36 |

| Tipo Type | Misure mm Dimensions mm | Misura mm | | | | Peso Weight Kg |
|-----------------|----------------------------|-----------|-----|-----|-----|----------------------|
| | | A | B | C | D | |
| G-CTV75 | 5/700 | 1140 | 517 | 920 | 600 | 159 |
| G-CTV100 | 6/700 | 1218 | 595 | 920 | 600 | 168 |
| G-CTV125 | 8/700 | 1379 | 751 | 920 | 600 | 182 |
| G-CTV150 | 10/700 | 1570 | 907 | 920 | 600 | 197 |

