

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Capacity

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics						Portata • Capacity										
	HP	KW	A	μF	DNA	DNM	m³/h	0	6	8,4	12	14,4	16,8	19,2	22,8	25,2	27,6
							l/min	0	100	140	200	240	280	320	380	420	460

Prevalenza manometrica totale in metri • Total manometric head in meters

2 elettropompe esterne verticali multistadio • 2 external vertical multistage electric pumps																	
GAU-CTV30	8/230	3-3	2,2-2,2	5,3-5,3	1"½	3"	75	72	69	65	59	55	49	37	29	20	
GAU-CTV40	11/230	4-4	3-3	6,8-6,8	1"½	3"	103	100	97	91	85	78	70	56	46	33	

A richiesta con elettropompa pilota • Available, on request, with jockey electric pump

A richiesta, quadro autoalimentato con sirena e lampeggiante • Available, on request, with self-powered control box including siren and flashing light

Tipo Type	Misure mm Dimensions mm	Misura				Peso Weight Kg
		A	B	C	D	
GAU-CTV30	8/230	931	794	1000	850	130
GAU-CTV40	11/230	1071	902	1000	850	146

