

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Capacity

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics						Portata • Capacity											
	HP	KW	A	µF	DNA	DNM	m³/h	0	12	14,4	16,8	19,2	22,8	25,2	27,6	31,2	36	39,6
							l/min	0	200	240	280	320	380	420	460	520	600	660

Prevalenza manometrica totale in metri • Total manometric head in meters

2 elettropompe esterne verticali multistadio • 2 external vertical multistage electric pumps																		
GAU-CTV30	5/330	3-3	2,2-2,2	5,3-5,3	1"½	3"	49	46	44	43	41	38	35	33	28	20	14	
GAU-CTV40	7/330	4-4	3-3	6,8-6,8	1"½	3"	68	63	61	58	56	52	49	45	39	29	20	
GAU-CTV55	10/330	5,5-5,5	4-4	8,5-8,5	1"½	3"	102	94	91	88	84	77	72	66	57	42	29	

A richiesta con elettropompa pilota • Available, on request, with jockey electric pump

A richiesta, quadro autoalimentato con sirena e lampeggiante • Available, on request, with self-powered control box including siren and flashing light

Tipo Type	Misure mm Dimensions mm	Misura				Peso Weight Kg
		A	B	C	D	
GAU-CTV30	5/330	823	686	1000	850	126
GAU-CTV40	7/330	927	758	1000	850	141
GAU-CTV55	10/330	1035	866	1000	850	146

