

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

Portata • Capacity

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics						Portata • Capacity											
	HP	KW	A	µF	DNA	DNM	m³/h	0	22,8	27,6	31,2	36	39,6	43,2	48	54	60	66
							l/min	0	380	460	520	600	660	720	800	900	1000	1100

Prevalenza manometrica totale in metri • Total manometric head in meters

2 elettropompe esterne verticali multistadio • 2 external vertical multistage electric pumps																		
GAU-CTV55	6/530	5,5-5,5	4-4	8,5-8,5	2"½	4"	60	53	50	49	46	43	40	35	27	18	7	
GAU-CTV75	8/530	7,5-7,5	5,5-5,5	13-13	2"½	4"	80	70	67	65	61	58	53	47	37	24	9	
GAU-CTV100	11/530	10-10	7,5-7,5	16,5-16,5	2"½	4"	110	97	92	89	84	79	73	64	49	33	13	
GAU-CTV125	14/530	12,5-12,5	9,2-9,2	19,2-19,2	2"½	4"	139	123	118	113	107	101	93	81	64	43	17	

A richiesta con elettropompa pilota • Available, on request, with jockey electric pump

A richiesta, quadro autoalimentato con sirena e lampeggiante • Available, on request, with self-powered control box including siren and flashing light

Tipo Type	Misure mm Dimensions mm	Misura				Peso Weight Kg
		A	B	C	D	
GAU-CTV55	6/530	1068	927	1000	850	165
GAU-CTV75	8/530	1220	1027	1000	850	196
GAU-CTV100	11/530	1370	1177	1000	850	207
GAU-CTV125	14/530	1525	1327	1000	850	221

