

Elettropompe sommergibili per acque luride

Electric submersible pumps for sewage water

SEMISOM /65

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

50 Hz M = 1~ 230 V T = 3~ 400 V		Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Passaggio solidi Solids passage ø		P o r t a t a • F l o w														
										HP	KW	A max	µF	m	DNM	m³/h	0	6	12	18	24	30	36	42
										Prevalenza manometrica totale in metri • Total manometric head in meters														
Girante arretrata • Vortex impeller																								
SEMISOM 1100/65 T		3	2,2	6		10	3"	65	13	12	11	9,5	8,5	7	5,5	4	2,5	1						
SEMISOM 1300/65 T		4,5	3,4	8,1		10	3"	65	18,5	17	16	14,5	13	11,5	10	8,5	7	5,5	3,5	2				
Girante bicanale • Double-Channel impeller																								
SEMISOM 1500/65 T		4,5	3,4	9		10	3"	65	19,5	18,5	17,5	16,5	15,5	14,5	13,5	12	11	10	8,5	7	4,5	1,5		

A richiesta dispositivo di discesa ed ancoraggio • Available, on request descent and anchorage device

Tipo Type	Misure mm Dimensions mm				Peso Weight Kg
	A	B	C	D	
SEMISOM 1100/65 T	584	65	417	222	40,2
SEMISOM 1300/65 T	609	65	417	222	42,9
SEMISOM 1500/65 T	609	65	417	222	44,4

