

Elettropompe sommergibili 4 poli per acque luride

Electric submersible pumps 4 poles for sewage water

Caratteristiche tecniche 4 poli 50 Hz • Performance characteristics 4 poles 50 Hz

		P o r t a t a • F l o w																			
50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable m	DNM	Passaggio solidi Solids passage ø	P o r t a t a • F l o w													
	HP	KW	A max	µF				m³/h	0	6	12	18	24	27	30	33	36	39	42	45	
		P r e v a l e n z a m a n o m e t r i c a t o t a l e i n m e t r i • T o t a l m a n o m e t r i c h e a d i n m e t e r s																			
Girante arretrata • Vortex impeller																					
SEMISOM 754/65 M	1,6	1,2	7,7	31,5	10	3"	65	7,8	7,3	6,7	6,2	5,5	5,1	4,6	4,2	3,7	3,2	2,5	1,9		
SEMISOM 754/65 T	1,6	1,2	3,3		10	3"	65	7,8	7,3	6,7	6,2	5,5	5,1	4,6	4,2	3,7	3,2	2,5	1,9		

I modelli monofase sono disponibili con o senza galleggiante • Single-phase electric pumps are available with or without float switch

A richiesta dispositivo di discesa ed ancoraggio • Available, on request, descent and anchorage device

Tipo Type	Misure mm Dimensions mm				Peso Weight Kg
	A	B	C	D	
SEMISOM 754/65 M	569	65	417	222	43,3
SEMISOM 754/65 T	569	65	417	222	43

