

# Elettropompe sommergibili 4 poli per acque luride 60 Hz

## Electric submersible pumps 4 poles for sewage water 60Hz

**SEMISOM /65** 

Caratteristiche tecniche 2 poli 60 Hz • Performance characteristics 2 poles 60 Hz

		P o r t a t a • F l o w																			
60 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Passaggio solidi Solids passage ø	P r e v a l e n z a m a n o m e t r i c a t o t a l e i n m e t r i • T o t a l m a n o m e t r i c h e a d i n m e t e r s													
	HP	KW	A max	µF	m	DNM		m³/h	0	6	12	18	24	27	30	33	36	39	42	45	48
		P r e v a l e n z a m a n o m e t r i c a t o t a l e i n m e t r i • T o t a l m a n o m e t r i c h e a d i n m e t e r s																			
		P r e v a l e n z a m a n o m e t r i c a t o t a l e i n m e t r i • T o t a l m a n o m e t r i c h e a d i n m e t e r s																			
Girante arretrata • Vortex impeller																					
SEMISOM 754/65 M	1,6	1,2	7,7	25	10	3"	65	8,5	7,8	7	6,2	5,5	5,1	4,6	4,2	3,8	3,4	3	2,6	2,1	
SEMISOM 754/65 T	1,6	1,2	3,2		10	3"	65	8,5	7,8	7	6,2	5,5	5,1	4,6	4,2	3,8	3,4	3	2,6	2,1	

I modelli monofase sono disponibili con o senza galleggiante • Single-phase electric pumps are available with or without float switch

A richiesta dispositivo di discesa ed ancoraggio • Available, on request, descent and anchorage device

Tipo Type	Misure mm Dimensions mm				Peso Weight Kg
	A	B	C	D	
SEMISOM 754/65 M	569	65	417	222	43,3
SEMISOM 754/65 T	569	65	417	222	43,0

