

Elettropompe sommergibili per acque luride 60 Hz

Electric submersible pumps for sewage water 60 Hz

SEMISOM L-SL

Caratteristiche tecniche 2 poli 60 Hz • Performance characteristics 2 poles 60 Hz

Portata • Flow

60 Hz M = 1- 230 V T = 3- 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable m	Passaggio solidi Solids passage ø	Portata • Flow												
	HP	KW	A max	µF			m ³ /h	0	1,8	6	9	12	15	18	21	24	27	30	39
							l/min	0	30	100	150	200	250	300	350	400	450	500	650

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante arretrata • Vortex impeller

SEMISOM 265 L M	0,75	0,55	4,25	12,5	5	1 1/2"	40	8,2	7,5	6	5	4	2,7	1,5						
SEMISOM 365 L M	1	0,75	6	20	5	1 1/2"	40	10,5	10	8,5	7,5	6,5	5,5	4	2	0,5				
SEMISOM 450 L M	1,5	1,1	6,8	20	5	2"	50	10,5	10	9,5	9	8	7	6,5	5	4,5	3	2		
SEMISOM 265 L T	0,75	0,55	1,7		5	1 1/2"	40	8,2	7,5	6	5	4	2,7	1,5						
SEMISOM 365 L T	1	0,75	2,4		5	1 1/2"	40	10,5	10	8,5	7,5	6,5	5,5	4	2	0,5				
SEMISOM 450 L T	1,5	1,1	2,6		5	2"	50	10,5	10	9,5	9	8	7	6,5	5	4,5	3	2		

Girante bicanale • Double-Channel impeller

SEMISOM 262 SL M	0,75	0,55	4	12,5	5	2"	32	13	12	11	10	9	7,5	6,5	5	4	3			
SEMISOM 635 SL M	1,5	1,1	6	20	5	2"	32	16,5	16	14,5	13,5	12,5	11,5	10,5	9	8	6,5	5,5	1,5	
SEMISOM 262 SL T	0,75	0,55	1,6		5	2"	32	13	12	11	10	9	7,5	6,5	5	4	3			
SEMISOM 635 SL T	1,5	1,1	2,3		5	2"	32	16,5	16	14,5	13,5	12,5	11,5	10,5	9	8	6,5	5,5	1,5	

I modelli monofase sono disponibili con o senza galleggiante • Single-phase electric pumps are available with or without float switch

Tipo Type		Misure mm Dimensions mm				Peso Weight Kg
		A	B	C	D	
SEMISOM 265 L M		400	50	230	162	13,6
SEMISOM 365 L M		440	50	230	162	16,6
SEMISOM 450 L M		464	50	260	183	19,4
SEMISOM 265 L T		400	50	230	162	13,5
SEMISOM 365 L T		440	50	230	162	16,2
SEMISOM 450 L T		464	50	260	183	19,2
SEMISOM 262 SL M		400	60	250	172	16,7
SEMISOM 635 SL M		440	60	250	172	19,3
SEMISOM 262 SL T		400	60	250	172	16,0
SEMISOM 635 SL T		440	60	250	172	19,0

