

Elettropompe sommergibili per acque torbide 60 Hz

Electric submersible pumps for dirty water 60 Hz



Caratteristiche tecniche 2 poli 60 Hz • Performance characteristics 2 poles 60 Hz

		P o r t a t a • F l o w																														
60 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		Passaggio solidi Solids passage ø		m³/h										l/min													
	HP	KW	A max	µF	m	DNM	mm	inch	0	1,8	6	9	12	15	18	21	24	27	0	30	100	150	200	250	300	350	400	450				
		Prevalenza manometrica totale in metri • Total manometric head in meters																														
		Girante aperta • Open impeller																														
SEMISOM 190	M	0,5	0,37	2,45	8	5	1"¼	5	10,5	9,5	6,5	4	1																			
SEMISOM 320	M	0,75	0,55	4	12,5	5	1"¼	13	14	13	11,5	10	7,5	5	3																	
SEMISOM 465	M	1,5	1,1	6	20	5	2"	5	19	18	16	15	13,5	12	10	7,5	5,5	1														
SEMISOM 320	T	0,75	0,55	1,6		5	1"¼	13	14	13	11,5	10	7,5	5	3																	
SEMISOM 465	T	1,5	1,1	2,5		5	2"	5	19	18	16	15	13,5	12	10	7,5	5,5	1														

I modelli monofase sono disponibili con o senza galleggiante • Single-phase electric pumps are available with or without float switch

Tipo Type		Misure mm Dimensions mm				Peso Weight Kg
		A	B	C	D	
SEMISOM 190	M	335	50	225	164	10,8
SEMISOM 320	M	360	50	225	164	13,0
SEMISOM 465	M	440	60	250	172	19,5
SEMISOM 320	T	360	50	225	164	12,8
SEMISOM 465	T	440	60	250	172	19,2

