

Elettropompe sommerse per pozzi da 6" (150 mm)

Electric submersible pumps for 6" (150 mm) wells

SR /400 /700 

Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

P o r t a t a • F l o w

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		P o r t a t a • F l o w																										
	HP	KW	A	µF	m	DNM	m³/h	0	11,4	12,6	13,8	15,6	18	19,8	24	27	30	33	36	42	l/min	0	190	210	230	260	300	330	400	450	500	550	600

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante radiale • Radial impeller																											
SRT40 4/400	4	3	7,6	5	2"	50	41	40	37	35	31	28	20	14													
SRT55 5/400	5,5	4	10	5	2"	64	52	51	49	46	42	38	29	20													
Girante semiassiale • Semi-Axial impeller																											
SRT55 3/700	5,5	4	10	5	2"	41						35	34	31	28	25	22	18	9								

Tipo Type	Misure mm Dimensions mm			Peso Weight Kg
	A	B	C	
SRT40 4/400	1185	60	142	41,5
SRT55 5/400	1284	60	142	46
SRT55 3/700	1262	60	142	40,5

