

# Elettropompe sommerse per pozzi da 6" (150 mm)

## Electric submersible pumps for 6" (150 mm) wells



Caratteristiche tecniche 2 poli 50 Hz • Performance characteristics 2 poles 50 Hz

P o r t a t a • F l o w

50 Hz M = 1~ 230 V T = 3~ 400 V	Caratteristiche Nominali Nominal Characteristics				Cavo Cable		P o r t a t a • F l o w										
	HP	KW	A	µF	m	DNM	m³/h	0	0,36	0,6	0,72	0,9	1,08	1,32	1,5	1,8	2,4
							l/min	0	6	10	12	15	18	22	25	30	40

Prevalenza manometrica totale in metri • Total manometric head in meters

Girante periferica • Peripheral impeller																		
TURBOSOM	57 M	0,75	0,55	3,8	16	10	1"	60	54	50	48	44	40	35	31	25	11	
TURBOSOM	77 M	1	0,75	6	20	10	1"	84	75	69	66	61	56	49	44	35	17	
TURBOSOM	57 T	0,75	0,55	1,6		10	1"	63	57	52	50	46	42	37	33	26	11	
TURBOSOM	77 T	1	0,75	2,3		10	1"	85	76	70	67	62	57	51	46	37	19	

Tipo Type	Misure mm Dimensions mm			Peso Weight Kg
	A	B	C	
TURBOSOM 57 M	334	236	136	12,6
TURBOSOM 77 M	349	251	136	14
TURBOSOM 57 T	334	236	136	12,6
TURBOSOM 77 T	349	251	136	13,7

